



CUMMINS INC.
Columbus, IN 47201
Marine Performance Curves
marine.cummins.com

Basic Engine Model
QSM11-M-355 CON
Engine Configuration
D353021MX03

Curve Number:
M-20777
CPL Code:
4334
Date:
27-Oct-16


Displacement: **10.8 liter [661 in³]** Rated Power: **260 kw [349 bhp, 355 mhp]**
Bore: **125 mm [4.92 in]** Rated Speed: **1800 rpm**
Stroke: **147 mm [5.79 in]** Rating Type: **Continuous Duty**
Fuel System: **CELECT** Aspiration: **Turbocharged / Sea Water Aftercooled**
Cylinders: **6**

CERTIFIED: This diesel engine complies with or is certified to the following agencies requirements:

EPA Tier 3 - Model year requirements of the EPA marine regulation (40CFR1042)

EU Stage IIIa - EC Nonroad Mobile Machinery Directive (2004/26/EC)

IMO Tier II - Tier 2 (Two) NOx requirements of International Maritime Organization (IMO), MARPOL 73/78 Annex VI, Regulation 13



Speed	Full Throttle- Power		Full Throttle- Torque		Fuel Cons.- Prop. Curve 3.0 Exp.	
	rpm	kw (hp)	N·m (ft-lb)	L/hr (gal/hr)		
1850	260	(349)	1343	(990)		
1800	260	(349)	1380	(1018)	67.6	(17.9)
1700	259	(348)	1457	(1075)	55.8	(14.7)
1600	257	(344)	1532	(1130)	46.3	(12.2)
1500	253	(340)	1613	(1190)	38.3	(10.1)
1400	248	(333)	1695	(1250)	31.2	(8.2)
1300	231	(309)	1695	(1250)	25.0	(6.6)
1200	213	(286)	1695	(1250)	19.8	(5.2)
1100	192	(258)	1668	(1230)	15.5	(4.1)

* Cummins Full Throttle Requirements:

- Engine achieves or exceeds rated rpm at full throttle under any steady operating condition
- Engines in variable displacement boats (such as pushboats, tugboats, net dragners, etc.) achieve no less than 100 rpm below rated speed at full throttle during a dead push or bollard pull
- Engine achieves or exceeds rated rpm when accelerating from idle to full throttle

Rated Conditions: Ratings are based upon ISO 15550 reference conditions; air pressure of 100 kPa [29.612 in Hg], air temperature 25deg. C [77 deg. F] and 30% relative humidity. Power is in accordance with IMCI procedure. Member NMMA. Unless otherwise specified, tolerance on all values is +/-5%.

Full Throttle curve represents power at the crankshaft for mature gross engine performance corrected in accordance with ISO 15550. Propeller Curve represents approximate power demand from a typical propeller. Propeller Shaft Power is approximately 3% less than rated crankshaft power after typical reverse/reduction gear losses and may vary depending on the type of gear or propulsion system used.

Fuel Consumption is based on fuel of 35 deg. API gravity at 16 deg C [60 deg. F] having LHV of 42,780 kJ/kg [18390 Btu/lb] and weighing 838.9 g/liter [7.001 lb/U.S. gal].

Continuous Rating (CON): Intended for continuous use in applications requiring uninterrupted service at full power. This rating is an ISO 15550 standard power rating.

TECHNICAL DEPT.

CHIEF ENGINEER

Propulsion Marine Engine Performance Data

Curve No. M-20777
DS : 3075
CPL : 4334
DATE: 27-Oct-16

General Engine Data

Engine Model		QSM11-M-355 CON
Rating Type		Continuous Duty
Rated Engine Power	kW [hp]	260 [349]
Rated Engine Speed	rpm	1800
Rated Power Production Tolerance	±%	5
Rated Engine Torque	N·m [lb·ft]	1381 [1018]
Peak Engine Torque @ 1200 rpm.....	N·m [lb·ft]	1695 [1250]
Brake Mean Effective Pressure	kPa [psi]	1603 [232]
Indicated Mean Effective Pressure.....	kPa [psi]	1782 [258]
Maximum Allowable Engine Speed	rpm	1860
Maximum Torque Capacity from Front of Crank ²	N·m [lb·ft]	847 [625]
Compression Ratio		15.9:1
Piston Speed	m/sec [ft/min]	8.8 [1736]
Firing Order		1-5-3-6-2-4
Weight (Dry) - Engine Only - Average	kg [lb]	1118 [2464]
Weight (Dry) - Engine With Heat Exchanger System - Average.....	kg [lb]	1184 [2610]

Governor Settings

High Speed Governor Break Point.....	rpm	1850
Minimum Idle Speed Setting	rpm	600
Normal Idle Speed Variation	±rpm	10
High Idle Speed Range Minimum	rpm	1840
Maximum	rpm	1860

Noise and Vibration

Average Noise Level - Top	(Idle).....	dBA @ 1m	80
	(Rated).....	dBA @ 1m	95
Average Noise Level - Right Side	(Idle).....	dBA @ 1m	80
	(Rated).....	dBA @ 1m	95
Average Noise Level - Left Side	(Idle).....	dBA @ 1m	80
	(Rated).....	dBA @ 1m	95
Average Noise Level - Front	(Idle).....	dBA @ 1m	80
	(Rated).....	dBA @ 1m	95

Fuel System¹

Avg. Fuel Consumption - ISO 8178 E3 Standard Test Cycle	l/hr [gal/hr]	46.1 [12.2]
Fuel Consumption at Rated Speed	l/hr [gal/hr]	67.6 [17.9]
Approximate Fuel Flow to Pump	l/hr [gal/hr]	219.6 [58.0]
Maximum Allowable Fuel Supply to Pump Temperature	°C [°F]	60.0 [140]
Approximate Fuel Flow Return to Tank	l/hr [gal/hr]	152.0 [40.1]
Approximate Fuel Return to Tank Temperature	°C [°F]	71.2 [160]
Maximum Heat Rejection to Drain Fuel	kW [Btu/min]	2.4 [138]
Fuel Pressure - Pump Out/Rail . Mechanical Gauge	kPa [psi]	1103 [160]

TBD= To Be Determined

N/A = Not Applicable

N.A. = Not Available

¹ Unless otherwise specified, all data is at rated power conditions and can vary ± 5%.

² No rear loads can be applied when the FPTO is fully loaded. Max PTO torque is contingent on torsional analysis results for the specific drive system. Consult Installation Direction Booklet for Limitations.

³ Heat rejection to coolant values are based on 50% water/50% ethylene glycol mix and do NOT include fouling factors. If sourcing your own cooler, a service fouling factor should be applied according to the cooler manufacturer's recommendation.

⁴ Consult option notes for flow specifications of optional Cummins seawater pumps, if applicable.

⁵ May not be at rated load and speed. Maximum heat rejection may occur at other than rated conditions.

CUMMINS INC.

COLUMBUS, INDIANA

All Data is Subject to Change Without Notice - Consult the following Cummins Web site for the most recent data:

<http://marine.cummins.com/>

Propulsion Marine Engine Performance Data

Curve No. M-20777
 DS : 3075
 CPL : 4334
 DATE: 27-Oct-16

Air System¹

Intake Manifold Pressure	kPa [in Hg]	169 [50]
Intake Air Flow	l/sec [cfm]	399 [845]
Heat Rejection to Ambient	kW [Btu/min]	19 [1094]

Exhaust System¹

Exhaust Gas Flow	l/sec [cfm]	755 [1600]
Exhaust Gas Temperature (Turbine Out)	°C [°F]	385 [724]
Exhaust Gas Temperature (Manifold)	°C [°F]	559 [1038]

Emissions (in accordance with ISO 8178 Cycle E3)

NO _x (Oxides of Nitrogen)	g/kw·hr [g/hp·hr]	4.90 [3.65]
HC (Hydrocarbons)	g/kw·hr [g/hp·hr]	0.31 [0.23]
CO (Carbon Monoxide)	g/kw·hr [g/hp·hr]	0.34 [0.25]
PM (Particulate Matter)	g/kw·hr [g/hp·hr]	0.02 [0.02]

Cooling System¹

Sea Water Pump Specifications	MAB 0.08.17-07/16/2001	
Pressure Cap Rating (With Heat Exchanger Option)	kPa [psi]	103 [15]

Engines without Low Temperature Aftercooling (LTA)

Sea Water Aftercooled Engine (SWAC)

Coolant Flow to Engine Heat Exchanger	l/min [gal/min]	181 [47.9]
Standard Thermostat Operating Range (Start to Open)	°C [°F]	71 [160]
Standard Thermostat Operating Range (Full Open)	°C [°F]	80 [175]
Heat Rejection to Engine Coolant ³	kW [Btu/min]	258 [14700]

TBD= To Be Determined

N/A = Not Applicable

N.A. = Not Available

¹ Unless otherwise specified, all data is at rated power conditions and can vary ± 5%.

² No rear loads can be applied when the FPTO is fully loaded. Max PTO torque is contingent on torsional analysis results for the specific drive system. Consult Installation Direction Booklet for Limitations.

³ Heat rejection to coolant values are based on 50% water/50% ethylene glycol mix and do NOT include fouling factors. If sourcing your own cooler, a service fouling factor should be applied according to the cooler manufacturer's recommendation.

⁴ Consult option notes for flow specifications of optional Cummins seawater pumps, if applicable.

⁵ May not be at rated load and speed. Maximum heat rejection may occur at other than rated conditions.

CUMMINS INC.

COLUMBUS, INDIANA

All Data is Subject to Change Without Notice - Consult the following Cummins Web site for the most recent data:

<http://marine.cummins.com/>