



**Fire  
Power**

## Engine Specification Sheet

Cummins Fire Power

De Pere, WI 54115

<http://www.cumminsfirepower.com>

## Basic Engine Model


**CFP33-F25, F35**

Curve Number:

**FR - 30203**

Revision Date:

**March 2010**



### Operating Speed (RPM)

Model	2600
CFP33-F25	62 (46)
CFP33-F35	77 (57)



Ratings are: HP (kW)

### Specifications

Aspiration.....	Turbocharged
Rotation.....	Counter clockwise from flywheel end
Weight - lb (kg) Est.....	800 (360)
Displacement - in <sup>3</sup> (litre).....	199 (3.3)
Engine Type.....	4 Cycle; In-Line, 4 Cylinder
Engine Series.....	Cummins B3.3 Series
Exhaust Emissions.....	EPA/CARB Tier 2

Equipment	Standard	Optional
Air Cleaner	Disposable, Direct Mounted, Indoor Service	N/A
Alternator	12V-DC, 35 AMPS; With Belt Guard	N/A
Cooling Loop	N/A	Maximum Pressure of 400 PSI
Exhaust Protection	Metal Guards on Manifolds and Turbo	N/A
Exhaust Flex Connection	SS Flex, NPT	SS Flex, 150# Flange
Flywheel Power Take-Off	Flywheel	•Drive Shaft System •Stub Shaft
Fuel Connections	Fire Resistant Flexible Supply and Return Lines	N/A
Fuel Injection	Direct Injection	N/A
Fuel Filter	Primary Filter with Priming Pump	N/A
Engine Heater	120V-AC, 1500 Watts	240V-AC, 1500 Watts
Governor, Speed	Constant Speed	N/A
Heat Exchanger	Tube & Shell Type, 60 PSI with NPTF Connections	N/A
Instrument Panel	English and Metric, Tachometer, Hourmeter, Water Temperature, Oil Pressure & Two (2) Voltmeters	N/A
Junction Box	Integral with Instrument Panel; For DC Wiring Interconnection to Engine Controller	N/A
Lube Oil Cooler	Engine Water Cooled, Plate Type	N/A
Lube Oil Filter	Full Flow with By-Pass Valve	N/A
Lube Oil Pump	Gear Driven	N/A
Manual Start	On Instrument Panel	N/A
Overspeed Controls	Electronic with Reset & Test on Instrument Panel	N/A
Raw Water Solenoid Operation	Automatic from Engine Controller & from Emergency Local Control	N/A
Run-Stop Control	On Instrument Panel	N/A
Run Solenoid	12V-DC	N/A
Starters	12V-DC	N/A
Throttle Control	Adjustable Speed Control	N/A
Water Pump	Vee Belt Drive with Guard	N/A





## Engine Ratings Baselines

- Engines are rated at standard SAE conditions of 29.61 in. (7521 mm) Hg barometer and 77°F (25°C) inlet air temperature (approximates 300ft. (91.4 m) above sea level) by the testing laboratory (see SAE Standard J1349).
- A deduction of 3 percent from engine horsepower rating at standard SAE conditions shall be made for diesel engines for each 1000 ft. (305 m) altitude above 300 ft. (91.4 m).
- A deduction of 1 percent from engine horsepower rating as corrected to standard SAE conditions shall be made for diesel engines for every 10°F above 77°F (24°C) ambient temperature.

## Certified Power

This Cummins Fire Power fire pump driver is built to comply with NFPA-20, and is UL listed and FM approved.

\* Subject to change without notification

For additional information, click the hyperlinks below.

[CFP33-F25](#)

[CFP33-F35](#)

**Fire  
Power****Engine Performance Curve****Cummins Fire Power**

DePere, WI 54115

<http://www.cumminsfirepower.com>**Basic Engine Model****CFP33-F25**Curve Number: **FR - 30005**Revision Date: **March 2010**

Engine Family:

**G-Drive**

Displacement - in.3 (litre):

**199 (3.3)**

Compression Ratio:

**17.5:1**

No. of Cylinders:

**4**

Fuel System:

**Zexel**

CPL Code:

**NA**

Emission Certification:

**2004 EPA/CARB Tier 2**

Aspiration:

**Turbocharged**

Engine Configuration:

**D782002GX03**


Minimum rating:

**62 HP @ 2600 RPM**


Maximum rating:

**62 HP @ 2600 RPM****Torque Output \***

RPM	lb-ft	N-m
2600	125	170

**Horsepower Output \***

RPM	BHP	kW
2600	62	46



\*CFP33-F25 is not a speed rated engine

1. Curves shown above represent mature gross engine performance capabilities obtained and corrected in accordance with SAE J1349 conditions of 29.61 in Hg (100 kPa) barometric pressure [300 ft. (91.4 m) altitude], 77 °F (25 °C) inlet air temperature, and 0.30 in. Hg (1 kPa) water vapor pressure with No. 2 diesel fuel.

2. The engine may be operated without changing the fuel setting up to 300 ft. (91.4 m) altitude and up to 77°F (25 °C) ambient temperature. For sustained operation at high altitudes, the fuel rate of the engine should be adjusted to limit performance by 3% per 1,000 ft. (305 m) above 300 ft. (91.4 m) altitude. For sustained operation at high ambient temperatures, the fuel rate of the engine should be adjusted to limit performance by 1% per 10 °F above 77 °F (2% per 11 °C above 25 °C).

3. Engine is certified at only 2600 RPM.

**Jim Vanden Boogard****Director of Engineering****Certified Within 5%**

	<b>Engine Datasheet</b> <b>Cummins Fire Power</b> De Pere, WI 54115 <a href="http://www.cumminsfirepower.com">http://www.cumminsfirepower.com</a>	Basic Engine Model <b>CFP33-F25, F35</b>	
		Curve Number: <b>FR - 30005</b>	CPL Code: <b>NA</b>
Configuration Number: <b>D782002GX033</b> Installation Drawing: <b>15541</b>		Engine Family: <b>G-Drive</b>	Revision Date: <b>March 2010</b>

### **General Engine Data**

Type.....	4 Cycle; In-Line; 4 Cylinder
Aspiration.....	Turbocharged
Bore & Stroke - in. (mm).....	3.74 x 4.53 (95 x 115)
Displacement - in. <sup>3</sup> (litre).....	199 (3.3)
Compression Ratio.....	18.3:1
Valves per Cylinder - Intake.....	1
- Exhaust.....	1
Maximum Allowable Bending Moment @ Rear Face of Block - lb.-ft. (N-m).....	918 (1245)

### **Air Induction System**

Max. Temperature Rise Between Ambient Air and Engine Air Inlet - °F (°C).....	18 (10.0)
Maximum Inlet Restriction with Dirty Filter - in. H <sub>2</sub> O (mm H <sub>2</sub> O).....	30 (762)
Recommended Air Cleaner Element - (Standard).....	FLG Industrial AH1138

### **Lubrication System**

Oil Pressure Range at Rated - PSI (kPa) .....	50-80 (345-551)
Oil Capacity of Pan (High - Low) - U.S. quarts (litre) .....	7.4-5.8 (7.0-5.5)
Total System Capacity - U.S. Gal. (litre) .....	2.1 (8)
Recommended Lube Oil Filter .....	Fleetguard (Cummins)..... LF16011 (C6002112110)

### **Cooling System**

Raw Water Working Pressure Range at Heat Exchanger - PSI (kPa) .....	60 (413) MAX
Recommended Min. Water Supply Pipe Size to Heat Exchanger - in. (mm).....	0.75 (19.05)
Recommended Min. Water Disch. Pipe Size From Heat Exchanger - in. (mm).....	1.00 (25.40)
Coolant Water Capacity (Engine Side) - U.S. quarts (litre) .....	9.3 (8.8)
Standard Thermostat - Type.....	Modulating
- Range - deg F (deg C) .....	180-203 (82-95)
Minimum Raw Water Flow	
with Water Temperatures to 90 °F (32 °C) - U.S. GPM (litre/s) .....	12 (0.76)
Recommended Cooling Water Filter.....	Fleetguard (Cummins)..... None

A jacket water heater is mandatory on this engine. The recommended heater wattage is 1500 down to 40 °F (4 °C).

### **Exhaust System**

Max. Back Pressure Imposed by Complete Exhaust System in in. H <sub>2</sub> O (kPa) .....	40.8 (10.2)
Exhaust Pipe Size Normally Acceptable - in. (mm) .....	3.0 (76)

### **Noise Emissions**

Top.....	91.6 dBa
Right Side.....	93.2 dBa
Left Side.....	93.2 dBa
Front.....	93.2 dBa
Exhaust.....	93.2 dBa

The noise emission values are estimated sound pressure levels at 3.3 ft. (1 m.).

**Fuel Supply / Drain System****2600**

CFP33-F35 Nominal Fuel Consumption - Gal./hr. (L/hr) .....	4.3 (16.1)	
CFP33-F25 Nominal Fuel Consumption - Gal./hr. (L/hr) .....	3.4 (13.0)	
Fuel Type .....	Number 2 Diesel Only	
Minimum Supply Line Size - in. (mm) .....	0.25	(6.35)
Minimum Drain Line Size - in. (mm) .....	0.125	(3.18)
Maximum Fuel Height above C/L Fuel Pump ft (m) .....	24	(7)
Recommended Fuel Filter - Primary .....	Fleetguard (Cummins).....	FS5114 (C6003112110)
- Secondary .....	None	
Maximum Restriction @ Lift Pump-Inlet - With Clean Filter - in. Hg (mm Hg) .....	3.0	(76)
Maximum Restriction @ Lift Pump-Inlet - With Dirty Filter - in. Hg (mm Hg) .....	8.0	(203)
Maximum Return Line Restriction - Without Check Valves - in. Hg (mm Hg) .....	15	(381)
Minimum Fuel Tank Vent Capability - ft <sup>3</sup> /hr (m <sup>3</sup> /hr) .....	12	(0.36)
Maximum Fuel Temperature @ Lift Pump Inlet - °F (°C) .....	158	(70)

**Starting and Electrical System****12V****24V**

Min. Recommended Batt. Capacity - Cold Soak at 0°F (-18°C) or Above		
Engine Only - Cold Cranking Amperes - (CCA) .....	900	24 volt
Engine Only - Reserve Capacity - Minutes .....	430	option is
Battery Cable Size (Maximum Cable Length Not to Exceed 5 ft. [1.5 m] AWG) .....	00	not
Maximum Resistance of Starting Circuit - Ohms .....	0.0012	offered
Typical Cranking Speed - RPM .....	120	
Alternator (Standard), Internally Regulated - Ampere .....	60	
Wiring for Automatic Starting (Negative Ground) .....	Standard	
Reference Wiring Diagram .....	16122	

**Performance Data**

All data is based on the engine operating with fuel system, water pump, lubricating oil pump, air cleaner, and alternator; not included are compressor, fan, optional equipment, and driven components. Data is based on operation at SAE standard J1394 conditions of 300 ft. (91.4 m) altitude, 29.61 in. (752 mm) Hg dry barometer, and 77 °F (25 °C) intake air temperature, using No.2 diesel or a fuel corresponding to ASTM-D2.

Altitude Above Which Output Should be Limited - ft. (m) .....	300	(91.4)
Correction Factor per 1000 ft. (305 m) above Altitude Limit .....	3%	
Temperature Above Which Output Should be Limited - °F (°C) .....	77	(25)
Correction Factor per 10 °F (11 °C) Above Temperature Limit .....	1%	(2%)

**Exhaust Emissions (EPA Tier T2) [Reference Emissions Data Doc. 9805]****g/kW-hr****g/BHP-hr**

Hydrocarbons (HC/OMHCE).....	0.35	0.26
Oxides of Nitrogen (NOx).....	5.85	4.36
Non-Methane Hydrocarbons + NOx (NMHC+NOx).....	6.20	4.62
Carbon Monoxide (CO).....	1.10	0.82
Particulate.....	0.26	0.19

## FM Approved and UL Listed Ratings for CFP33-F25, F35

### Engine Speed - RPM

**2600**

<b>CFP33-F35</b> Output - BHP (kW) .....	<b>77 (57)</b>
Ventilation Air Required for Combustion - CFM (litre/sec) .....	195 (92)
Exhaust Gas Flow - CFM (litre/sec) .....	475 (224)
Exhaust Gas Temperature - °F (°C) .....	1075 (579)
Engine Heat Rejection to Coolant- BTU/min. (kW) .....	2201 (39)
Engine Heat Rejection to Ambient - BTU/min. (kW) .....	881 (15)

<b>CFP33-F25</b> Output - BHP (kW) .....	<b>62 (46)</b>
Ventilation Air Required for Combustion - CFM (litre/sec) .....	166 (78)
Exhaust Gas Flow - CFM (litre/sec) .....	404 (191)
Exhaust Gas Temperature - °F (°C) .....	914 (490)
Engine Heat Rejection to Coolant- BTU/min. (kW) .....	1871 (33)
Engine Heat Rejection to Ambient - BTU/min. (kW) .....	749 (13)

All Data is Subject to Change Without Notice.

Director of Engineering: Jim Vanden Boogard  
Cummins Fire Power, De Pere, WI 54115 U.S.A.



# EPA Tier 2 Emission Data Fire Pump NSPS Compliant

## CFP33-F25 Fire Pump Driver

Type: 4 Cycle; In-Line; 4 Cylinder

Aspiration: Turbocharged, Charge Air Cooled

15 PPM Diesel Fuel													
RPM	BHP	Fuel Consumption		D2 Cycle Exhaust Emissions						Exhaust			
		Gal/Hr	L/hr	Grams per BHP - HR			Grams per kW - HR			Temperature		Gas Flow	
				NMHC+NOx	CO	PM	NMHC+NOx	CO	PM	°F	°C	CFM	L/sec
2600	62	3.4	12.9	4.238	0.820	0.170	5.683	1.100	0.228	914	490	404	191

The emissions values above are based on CARB approved calculations for converting EPA (500 ppm) fuel to CARB 15 ppm fuel.

300-500 PPM Diesel Fuel													
RPM	BHP	Fuel Consumption		D2 Cycle Exhaust Emissions						Exhaust			
		Gal/Hr	L/hr	Grams per BHP - HR			Grams per kW - HR			Temperature		Gas Flow	
				NMHC+NOx	CO	PM	NMHC+NOx	CO	PM	°F	°C	CFM	L/sec
2600	62	3.4	12.9	4.623	0.820	0.194	6.200	1.100	0.260	914	490	404	191

B3.3T Base Model Manufactured by Cummins Inc.  
- Using fuel rating 30203

Reference EPA Standard Engine Family: D782001CX03

**No special options needed to meet current regulation emissions for all 50 states**

### Test Methods:

EPA/CARB Nonroad emissions recorded per 40CFR89 (ref. ISO8178-1) and weighted at load points prescribed in Subpart E, Appendix A, for Constant Speed Engines (ref. ISO8178-4, D2).

### Diesel Fuel Specifications:

Cetane Number: 40-48  
Reference: ASTM D975 No. 2-D

### Reference Conditions:

Air Inlet Temperature: 25°C (77°F)  
Fuel Inlet Temperature: 40°C (104°F)  
Barometric Pressure: 100 kPa (29.53 in Hg)  
Humidity: 10.7 g/kg (75 grains H<sub>2</sub>O/lb) of dry air; required for NOx correction  
Restrictions: Intake Restriction set to a maximum allowable limit for clean filter; Exhaust Back Pressure set to maximum allowable limit.

**Tests conducted using alternate test methods, instrumentation, fuel or reference conditions can yield different results.**



# California ATCM Tier 2 Emission Data EPA Tier 2 Emission Data

## CFP33-F25 Fire Pump Driver

Type: 4 Cycle; In-Line; 4 Cylinder  
Aspiration: Turbocharged, Charge Air Cooled

15 PPM Diesel Fuel													
RPM	BHP	Fuel Consumption		D2 Cycle Exhaust Emissions						Exhaust			
		Gal/Hr	L/hr	Grams per BHP - HR			Grams per kW - HR			Temperature		Gas Flow	
				NMHC+NOx	CO	PM	NMHC+NOx	CO	PM	°F	°C	CFM	L/sec
2600	62	3.4	12.9	4.238	0.820	0.170	5.683	1.100	0.228	914	490	404	191

The emissions values above are based on CARB approved calculations for converting EPA (500 ppm) fuel to CARB (15 ppm) fuel.

300-500 PPM Diesel Fuel													
RPM	BHP	Fuel Consumption		D2 Cycle Exhaust Emissions						Exhaust			
		Gal/Hr	L/hr	Grams per BHP - HR			Grams per kW - HR			Temperature		Gas Flow	
				NMHC+NOx	CO	PM	NMHC+NOx	CO	PM	°F	°C	CFM	L/sec
2600	62	3.4	12.9	4.623	0.820	0.194	6.200	1.100	0.260	914	490	404	191

B3.3T Base Model Manufactured by Cummins Inc.  
- Using fuel rating 30203

Reference EPA Standard Engine Family: 7CEXL03.3ABB

No special options needed to meet current emission regulations for all 50 states

### Test Methods:

EPA/CARB Nonroad emissions recorded per 40CFR89 (ref. ISO8178-1) and weighted at load points prescribed in Subpart E, Appendix A, for Constant Speed Engines (ref. ISO8178-4, D2).

### Diesel Fuel Specifications:


Cetane Number: 40-48  
Reference: ASTM D975 No. 2-D

### Reference Conditions:

Air Inlet Temperature: 25°C (77°F)  
Fuel Inlet Temperature: 40°C (104°F)  
Barometric Pressure: 100 kPa (29.53 in Hg)  
Humidity: 10.7 g/kg (75 grains H<sub>2</sub>O/lb) of dry air; required for NOx corrector  
Restrictions: Intake Restriction set to a maximum allowable limit for clean filter; Exhaust Back Pressure set to maximum allowable limit.

Tests conducted using alternate test methods, instrumentation, fuel or reference conditions can yield different results.



	<b>Engine Materials and Construction</b> Cummins Fire Power DePere, WI 54115 <a href="http://www.cumminsfirepower.com">http://www.cumminsfirepower.com</a>	Basic Engine Model <b>CFP33-F35, F25</b>
	Configuration Number: <b>D782001CX03</b> Installation Drawing: <b>8701</b>	Curve Number: <b>FR - 30203</b> CPL Code: <b>Tier2B3.3T</b> Engine Family: <b>Construction</b> Revision Date: <b>June 2006</b>

<p style="text-align: center;"><b><u>Engine</u></b></p> <p><b>Camshaft</b>          Type.....Precision Ground          Material.....Forged Steel          Location.....In Block          Drive.....Gear</p> <p><b>Connecting Rods</b>          Type.....I-Beam, Fracture-split          Material.....Nickel Chrome Molybdenum</p> <p><b>Crankshaft</b>          Type.....Precision Ground          Material.....Forged Steel</p> <p><b>Crankshaft Main Bearings</b>          Type.....Precision Half Shells          Material.....Steel, Copper with Soft Metal Overlay</p> <p><b>Crankshaft Rod Bearings</b>          Type.....Precision Half Shells          Material.....Steel, Copper with Soft Metal Overlay</p> <p><b>Cylinder Block</b>          Type.....Parent bored, plateau honed          Material.....Cast Iron Alloy</p> <p><b>Cylinder Head</b>          Type.....1 Common, 8 Valve          Material.....Cast Iron Alloy</p> <p><b>Cylinder Liners</b>          Type.....Parent bored, plateau honed          Material.....Cast Iron from Block</p> <p><b>Pistons</b>          Type.....1 Piece Cast          Material.....Aluminum Alloy</p> <p><b>Piston Pins</b>          Type.....Fixed          Material.....Forged Steel</p> <p><b>Piston Rings</b>          First.....Chrome Coated Ductile Cast Iron          Second.....Keystone, Hardened Grey Cast Iron          Third.....Chrome Coated Composite</p> <p><b>Valves</b>          Type.....Poppet          Arrangement.....Overhead Valve          Number per Cylinder...1 Intake, 1 Exhaust          Mechanism Type.....Mechanical Rocker Arm          Lifter Type.....Solid Push Tube</p>	<p style="text-align: center;"><b><u>Air Handling</u></b></p> <p><b>Air Cleaner</b>          Type.....Single Element, Disposable          Material.....Cellulose</p> <p><b>Turbocharger</b>          Type.....Mitsubishi TD04          Design.....Wastegated</p> <p style="text-align: center;"><b><u>Cooling System</u></b></p> <p><b>Charge Air Cooler Heat Exchanger</b>          Type.....None          Material.....          Covers.....Not Applicable          Headers.....Not Applicable          Plumbing.....          Not Applicable          Tubes.....Not Applicable</p> <p><b>Coolant Heat Exchanger</b>          Type.....Tube and Shell          Material.....          Electrode.....Zinc          Headers.....Copper          Shell.....Copper          Tubes.....Copper</p> <p><b>Coolant Pump</b>          Type.....Centrifugal          Drive.....Belt, Multi VCC</p> <p><b>Thermostat</b>          Type.....Modulating          Quantity.....1</p> <p style="text-align: center;"><b><u>Fuel System</u></b></p> <p><b>Fuel Injection Pump</b>          Type.....Rotary Distributor          Drive.....Mechanical, Gear Driven</p> <p><b>Fuel Lift Pump</b>          Type.....Piston          Drive.....Mechanical, Gear Driven</p> <p style="text-align: center;"><b><u>Lubrication System</u></b></p> <p><b>Oil Pump</b>          Type.....Gerotor          Drive.....Gear</p> <p><b>Lubrication Cooler</b>          Type.....Plate          Material.....Braised Stainless Steel</p>
---	--

**TECHNICAL BULLETIN****15937RAF  
60 Red High Solids Air Dry Enamel****PRODUCT DESCRIPTION**

This product has been formulated to comply with Cummins' Engineering Standard #21055 and exhibits fast dry, good exterior durability, and is 3.50 VOC compliant.

**HANDLING & STORAGE**

The containers should be stored away from direct sunlight and heat. Freezing is not harmful if reheated gently to room temperature prior to use.

**PHYSICAL CHARACTERISTICS**

Weight per Gallon:	8.43 lbs. $\pm$ .2 lbs.
Weight Solids:	58.83% $\pm$ 1.0%
Volume Solids:	49.71% $\pm$ 1.0%
VOC:	Less than 3.50
Viscosity:	17 $\pm$ 2" @ #3 Zahn
Theoretical Coverage - sq. ft./gl. @ 1.0 mil dry film thickness:	797.3
Cure Schedule - Air Dry @ 77°F & 50% Relative Humidity:	
Dust Free:	15 - 30 minutes
Dry to Touch:	45 - 60 minutes
Dry to Handle:	Overnight
Dry Hard:	2 - 3 weeks
Gloss:	90° @ 1.5 mils

**ENVIRONMENTAL REPORT**

Volatile Content (Wt.%):	41.17%
Organic Volatile Content (Wt.%):	41.17%
Water Content (Wt.%):	0.00
Water Content (Vol.%):	0.00
VOC Minus Water:	3.50 maximum

**DIRECTIONS FOR USE**

Thoroughly agitate the paint before using. This is a 3.50 VOC compliant coating that requires no reduction. When testing this product for film properties, use Bonderite 1000 P60 type panels. Cure times may vary depending on environmental conditions and film thickness.

**PRECAUTIONS & SAFETY**

- Do not apply at temperatures below 50°F.
- Read all container labels.
- Read Material Safety Data Sheet.

**CLEAN-UP**

Clean equipment immediately after use with Aromatic or Ketone Solvents.

February 24, 2003

Date Printed: 11/28/2007

Page: 1

Product Code: 15937RAF  
 Product Name: 60 RED HIGH SOLIDS ENAMEL

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

(See top of page)

**2. COMPOSITION/INFORMATION ON INGREDIENTS**

This product contains one or more reported carcinogens or suspected carcinogens which are noted below and in Section 11.

This product contains a component or components that are Federally classified as a hazardous air pollutant.

Component/Exposure Limits	CAS#	% by Wt.
METHYL AMYL KETONE	110-43-0	20.18
ACGIH TLV/TWA - 50 PPM, 233 MG/M3		
OSHA PEL - 100 PPM, 465 MG/M3		
OTHER LIMITS:		
NIOSH REL/TWA : 100 PPM, 465 MG/M3		
XYLENE(PURE)	1330-20-7	7.82
ACGIH TLV/TWA - 100 PPM, 434 MG/M3; STEL: 150 PPM		
OSHA PEL - 100 PPM(TWA), 435 MG/M3(TWA)		
OTHER LIMITS:		
NIOSH REL: 100 PPM(TWA), 435 MG/M3(TWA)		
METHYL PROPYL KETONE	107-87-9	5.97
ACGIH TLV/TWA - NOT ESTABLISHED		
OSHA PEL - 200 PPM, 700MG/M3		
OTHER LIMITS:		
NIOSH REL/TWA: 150PPM, 530MG/M3		
ACGIH STEL/CEIL: 150PPM, 529MG/M3		
METHYL ISOAMYL KETONE	110-12-3	2.65
ACGIH TLV/TWA - 50 PPM, 234 MG/M3		
OSHA PEL - 100 PPM, 475 MG/M3		
OTHER LIMITS:		
NIOSH REL/TWA : 50 PPM, 240 MG/M3		
IRON (III) OXIDE	1309-37-1	0-10%
ACGIH TLV/TWA - 5 MG/M3 (Fume)		
OSHA PEL - 10 MG/M3 (Fume)		
ETHYLBENZENE	100-41-4	1.733
ACGIH TLV/TWA - 100 PPM, 434 MG/M3 STEL: 125PPM		
OSHA PEL - 100 PPM, 435 MG/M3		
OTHER INFORMATION: Listed by IARC as Group 2B, possibly carcinogenic to humans. See Section 11.		
OTHER LIMITS:		
NIOSH REL: 100 PPM(TWA), 435 MG/M3(TWA)		
TOLUENE	108-88-3	1.49
ACGIH TLV/TWA - 20 PPM, 75MG/M3		
OSHA PEL: 200PPM, STEL: 300PPM, 500PPM(CEIL)*		

Date Printed: 11/28/2007

Page: 2

Product Code: 15937RAF  
Product Name: 60 RED HIGH SOLIDS ENAMEL

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

\* For a 10 minute interval during an 8-hour shift.  
OTHER LIMITS:  
NIOSH REL: 100PPM(TWA), 375MG/M3(TWA)  
NIOSH STEL/CEIL: 150PPM, 560MG/M3

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW:**

Harmful if inhaled. May cause the following effects:  
Nose, throat and respiratory tract irritation. Allergic respiratory reaction.  
May cause lung damage. Eye and skin irritation. Allergic skin reaction.

#### **FLAMMABLE LIQUID**

Keep away from heat, sparks, and flame.  
Vapors may cause flash fire.  
Toxic gases/fumes are given off during burning or thermal decomposition.

#### **EYE CONTACT:**

Severe irritant. Prolonged contact may result in chemical  
burns to the eyes. Blindness may occur.

#### **SKIN CONTACT:**

Severe irritant. Contact with skin causes severe irritation  
and pain. Prolonged contact may result in chemical burns.  
Product may be absorbed through the skin in harmful amounts.

#### **PRIMARY ROUTES OF ENTRY:**

Skin absorption.  
Dermal and inhalation.

#### **INGESTION:**

If swallowed, consult a physician immediately.

#### **INHALATION:**

Anesthetic. Can cause irritation of the respiratory tract or  
acute nervous system depression characterized by the  
following progressive steps if severe overexposure is  
continued: headache, dizziness, staggering gait, confusion  
or unconsciousness.

#### **CHRONIC INFORMATION:**

See Section 11.

#### **CARCINOGENICITY:**

Date Printed: 11/28/2007

Page: 3

Product Code: 15937RAF  
Product Name: 60 RED HIGH SOLIDS ENAMEL

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

See Section 11.

**MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:**

Asthma and other respiratory ailments; chemical sensitization.

**4. FIRST AID MEASURES**

---

**EYE CONTACT:**

Flush immediately with large amounts of running water for at least 15 minutes while lifting eyelids. Take to a physician for medical treatment.

**SKIN CONTACT:**

Wash affected areas with soap and water. Remove contaminated clothing and wash before reuse. Consult a physician if irritation develops or persists.

**INGESTION:**

If swallowed, CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

**INHALATION:**

Remove from exposure. Restore breathing. Keep warm and quiet. Notify a physician.

**5. FIRE FIGHTING MEASURES**

---

**FIRE AND EXPLOSION PROPERTIES:**

**FLASH POINT (deg.F):**

45

**METHOD:**

Tag Closed Cup

**FLAMMABLE LIMITS % :**

Lower limit: 1.05

Upper limit: 8.7

**AUTOIGNITION TEMPERATURE:**

N/A

**EXTINGUISHING MEDIA:**

Carbon Dioxide, Dry Chemical or Foam.

**FIREFIGHTING PROCEDURES AND EQUIPMENT:**

Keep containers tightly closed. Isolate from heat,

Date Printed: 11/28/2007

Page: 4

Product Code: 15937RAF  
Product Name: 60 RED HIGH SOLIDS ENAMEL

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

electrical equipment, sparks and open flames. Closed container may explode when exposed to extreme heat. Do not apply to hot surfaces. Never use welding or cutting torch on or near product container (even empty) because product (even residue) can ignite explosively. Full protective equipment including self-contained breathing apparatus should be worn. Water spray may be ineffective. Water may be used to cool closed containers to prevent pressure build-up or possible autoignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable.

---

## **6. ACCIDENTAL RELEASE MEASURES**

---

### **STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED :**

Evacuate all non-essential personnel and remove all sources of ignition (flames, hot surfaces, electrical, static and frictional sparks). Ventilate area. Equip clean-up crew with appropriate protective equipment. Avoid breathing vapors. Avoid skin contact. Prevent entry into drains, sewers and waterways. Notify appropriate authorities if necessary. Contain and remove with inert absorbent and nonsparking tools.

---

## **7. HANDLING AND STORAGE**

---

### **HANDLING:**

Use only with adequate ventilation. Avoid prolonged breathing of vapors. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates that vapor/mist levels are below applicable exposure limits. Follow respirator manufacturer's directions for use. Use grounding and bonding connection when transferring material to prevent static discharge, fire or explosion. Avoid free fall of liquid in excess of a few inches. Use sparkproof tools and explosion proof equipment.

### **STORAGE:**

Do not store above 120 F or below 32 F. Store large quantities in buildings designed to comply with OSHA's 29 CFR 1910.106. Keep away from heat, sparks and open flame. Keep containers closed when not in use. Keep closures tight and upright to prevent leakage. Emptied containers may retain hazardous residue. Follow all hazard precautions in this data sheet until container is thoroughly cleaned or destroyed. To avoid spontaneous

Date Printed: 11/28/2007

Page: 5

Product Code: 15937RAF  
Product Name: 60 RED HIGH SOLIDS ENAMEL

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed container.

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **ENGINEERING CONTROLS:**

Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below current applicable OSHA safety and health requirements in the mixing, application and curing areas; and to remove decomposition products during welding and flame cutting on surfaces coated with this product.

### **RESPIRATORY PROTECTION:**

When spray applied and when used in limited ventilation areas, wear a NIOSH/MSHA approved organic vapor/particulate respirator designed to remove a combination of particulate, gas and vapor. When used in confined areas or poorly ventilated areas, use a NIOSH/MSHA approved air line type respirator or hood. During sanding or grinding operations, use a NIOSH approved particulate respirator to remove solid airborne particles of sanding dust. Use NIOSH approved respirators when flame cutting, welding or hazing material coated with this product. Observe OSHA regulations for respirator use (29 CFR 1910.134). Air monitoring of the workplace may be required to determine appropriate respirator selection.

### **EYE PROTECTION:**

Use safety eyewear with splash guards or side shields. A full face shield may be appropriate. Contact lenses should not be worn.

### **SKIN PROTECTION:**

It is good industrial hygiene practice to minimize skin contact. Chemical resistant gloves are required for prolonged or repeated contact. An apron may be appropriate to protect against skin contact. Prevent prolonged skin contact with contaminated clothing. Wash contaminated clothing before reuse.

### **OTHER PROTECTIVE EQUIPMENT AND GUIDLINES:**

Safety showers and eye wash stations should be available. Educate and train employees in the safe use of this product.

Date Printed: 11/28/2007

Page: 6

Product Code: 15937RAF  
Product Name: 60 RED HIGH SOLIDS ENAMEL

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

---

**9. PHYSICAL AND CHEMICAL PROPERTIES**

---

**PHYSICAL STATE:**

Liquid.

**APPEARANCE:**

Opaque.

**ODOR:**

Solvent odor.

**VOC (LB/GL):**

3.46 lb/gl

**VOC (grams/liter):**

415 g/l

**WEIGHT PER GALLON:**

8.4358 lb/gl

**SPECIFIC GRAVITY:**

1.0131

**%EXEMPT SOLVENT by WEIGHT:**

0

**%EXEMPT SOLVENT by VOLUME:**

0

**BOILING POINT (deg. F):**

213

**WATER SOLUBILITY:**

Negligible.

**FREEZING POINT (deg. F):**

N/A

---

**10. STABILITY AND REACTIVITY**

---

**STABILITY:**

Stable under normal conditions.

**HAZARDOUS POLYMERIZATION:**

Will not occur.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

May produce hazardous fumes when heated to decomposition as in welding. Fumes may contain the following:  
Carbon Monoxide, Carbon Dioxide and other toxic vapors depending upon the temperature reached.

**INCOMPATIBILITIES (MATERIALS TO AVOID):**

Strong oxidizers.

---

**11. TOXICOLOGICAL INFORMATION**

---

**ACUTE EFFECTS:**



Date Printed: 11/28/2007

Page: 7

Product Code: 15937RAF  
Product Name: 60 RED HIGH SOLIDS ENAMEL

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

**Toluene:**

LD50 Oral Rat = 5000mg/kg  
LC50 Inhalation Rat = 8000 ppm for 4 hours  
LD50 Dermal Rabbit = 14000mg/kg

**Xylene (Mixed Isomers):**

LD50 Oral Rat = 4300mg/kg  
LC50 Inhalation Rat = 6700 ppm for 4 hours  
LD50 Dermal Rabbit = >2000mg/kg

**Ethyl Benzene:**

Oral Rat LD50 = 3.5 g/kg  
Dermal Rabbit LD50 = 17 g/kg

Has not been tested as a whole for acute effects.

**CHRONIC EFFECTS:**

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage, liver and kidney damage. Long term overexposure effects are not currently known. There are reports that long-term repeated exposure to Xylene may result in some loss of hearing. There are reports that long-term repeated exposure to Toluene may result in some loss of hearing.

Has not been tested as a whole for chronic effects.

**CARCINOGENICITY:**

Contains Ethylbenzene which IARC has listed as Group 2B, possibly carcinogenic to humans, based upon laboratory animal studies.

Has not been tested as a whole for carcinogenicity effects.

**MUTAGENICITY:**

Has not been tested as a whole for mutagenicity effects.

**REPRODUCTIVE EFFECTS:**

Has not been tested as a whole for reproductive effects.

**DEVELOPMENTAL EFFECTS:**

Has not been tested as a whole for developmental effects.

**12. ECOLOGICAL INFORMATION**

Date Printed: 11/28/2007

Page: 8

Product Code: 15937RAF  
Product Name: 60 RED HIGH SOLIDS ENAMEL

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

**ECOLOGICAL EFFECTS:**

Has not been tested as a whole for ecological effects.

**13. DISPOSAL CONSIDERATIONS****DISPOSAL METHODS:**

Recycle, fuel blend or incinerate.  
Dispose of in accordance with applicable laws and regulations. It is the responsibility of the owner of the waste to dispose of it properly. Laboratory analysis is recommended to profile the waste for proper disposal determination.

**U.S E.P.A WASTE NUMBER AND DESCRIPTION:**

D001 Waste Paint

**HAZARDOUS WASTE CHARACTERISTICS:**

Ignitable.

**14. TRANSPORT INFORMATION****UN NUMBER:**

UN 1263

**DOT PROPER SHIPPING NAME:**

Paint

**DOT HAZARD CLASS:**

3

**DOT LABEL:**

Flammable Liquid

**DOT PACKAGING GROUP:**

PG II

**U.S POSTAL SERVICE:**

Will not handle.

**15. REGULATORY INFORMATION**

(Not meant to be all inclusive - selected regulations represented)

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372:

Date Printed: 11/28/2007

Page: 9

Product Code: 15937RAF  
Product Name: 60 RED HIGH SOLIDS ENAMEL

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

CAS#100-41-4 Ethyl Benzene  
CAS#1330-20-7 Xylene  
CAS#108-88-3 Toluene

**TSCA STATUS:**

All ingredients are listed on the TSCA inventory.

**STATE REGULATIONS:**

Toluene is listed by the State of California as a substance known to cause reproductive toxicity. The California Safe Drinking Water and Toxic Enforcement Act requires clear and reasonable warning be given before exposing any person to toluene. Toluene may also contain traces of benzene which the State of California has found to cause cancer. This product may contain chemicals that fall under individual state Right-to-Know regulatory requirements. See Section 2 for material listings. For details on regulatory requirements, contact the appropriate agency in your state.

**16. OTHER INFORMATION**

Date of issue: 11/28/2007

Last Revision Date: 11/23/05

**HMIS Information**

HEALTH: 2

FLAMMABILITY: 3

REACTIVITY: 1

PERSONAL PROTECTIVE EQUIPMENT: X

**DISCLAIMER:**

This MSDS is provided as an informational resource only. The information is received from a combination of sources, including raw material suppliers and is believed to be reliable and accurate. It does not intend to be all inclusive and shall only be used as a guide. Changing reporting requirements and other uncontrolled variables make it impossible to guarantee the accuracy of the information contained in this document. It is the responsibility of the user to verify its information as well as determine the proper personal protection based on conditions of use. The buyer assumes all responsibility for the use and handling of this product in accordance with the Federal, State and Local laws and regulations. Hentzen Coatings, Inc. makes no representation or warranty regarding the accuracy of this information nor that the information or data will not change.

# MATERIAL SAFETY DATA SHEET

B54AF407

09 00

## Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER

B54AF407

HMIS CODES

Health	2*
Flammability	3
Reactivity	1

PRODUCT NAME

MERCURY AIR-O-JET\* Enamel, Gray Flash Primer

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY  
101 Prospect Avenue N.W.  
Cleveland, OH 44115

EMERGENCY TELEPHONE NO.

(216) 566-2917

DATE OF PREPARATION

07-JAN-07

INFORMATION TELEPHONE NO.

(216) 566-2902

## Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

% by WT	CAS No.	INGREDIENT	UNITS	VAPOR PRESSURE
22	64742-89-8	V. M. & P. Naphtha		
		ACGIH TLV	300 ppm	12 mm
		OSHA PEL	300 ppm	
		OSHA PEL	400 ppm STEL	
1	25013-15-4	Vinyl Toluene		
		ACGIH TLV	50 ppm	1.1 mm
		ACGIH TLV	100 ppm STEL	
		OSHA PEL	100 ppm	
1	100-41-4	Ethylbenzene		
		ACGIH TLV	100 ppm	7.1 mm
		ACGIH TLV	125 ppm STEL	
		OSHA PEL	100 ppm	
		OSHA PEL	125 ppm STEL	
6	1330-20-7	Xylene		
		ACGIH TLV	100 ppm	5.9 mm
		ACGIH TLV	150 ppm STEL	
		OSHA PEL	100 ppm	
		OSHA PEL	150 ppm STEL	
22	14807-96-6	Talc		
		ACGIH TLV	2 mg/m3 as Resp. Dust	
		OSHA PEL	2 mg/m3 as Resp. Dust	
6	7727-43-7	Barium Sulfate		
		ACGIH TLV	10 mg/m3 as Dust	
		OSHA PEL	10 mg/m3 Total Dust	
		OSHA PEL	5 mg/m3 Respirable Fraction	
10	13463-67-7	Titanium Dioxide		
		ACGIH TLV	10 mg/m3 as Dust	
		OSHA PEL	10 mg/m3 Total Dust	
		OSHA PEL	5 mg/m3 Respirable Fraction	
5	1314-13-2	Zinc Oxide		
		ACGIH TLV	10 mg/m3 as Dust	
		OSHA PEL	10 mg/m3 Total Dust	
		OSHA PEL	5 mg/m3 Respirable Fraction	

Continued on page 2

=====  
Section 3 -- HAZARDS IDENTIFICATION  
=====

## ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.

EYE or SKIN contact with the product, vapor or spray mist.

## EFFECTS OF OVEREXPOSURE

EYES: Irritation.

SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

## SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

## MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

## CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

=====  
Section 4 -- FIRST AID MEASURES  
=====

EYES: Flush eyes with large amounts of water for 15 minutes.  
Get medical attention.

SKIN: Wash affected area thoroughly with soap and water.  
Remove contaminated clothing and launder before re-use.

INHALATION: If affected, remove from exposure. Restore breathing.  
Keep warm and quiet.

INGESTION: Do not induce vomiting.  
Get medical attention immediately.

=====  
Section 5 -- FIRE FIGHTING MEASURES  
=====

## FLASH POINT

50 F PMCC

## LEL

0.9

## UEL

11.0

## FLAMMABILITY CLASSIFICATION

RED LABEL -- Flammable, Flash below 100 F (38 C)

## EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

## SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Continued on page 3

=====  
Section 6 -- ACCIDENTAL RELEASE MEASURES  
=====

## STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

  
=====Section 7 -- HANDLING AND STORAGE  
=====

## STORAGE CATEGORY

DOL Storage Class IB

## PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Contents are FLAMMABLE. Keep away from heat, sparks, and open flame.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

  
=====Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION  
=====

## PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

## VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits.

Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

## RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

## PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

## EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

## OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

## =====

## Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

-----

PRODUCT WEIGHT	11.03 lb/gal	1321 g/l
SPECIFIC GRAVITY	1.33	
BOILING POINT	240 - 338 F	115 - 170 C
MELTING POINT	Not Available	
VOLATILE VOLUME	52 %	
EVAPORATION RATE	Slower than ether	
VAPOR DENSITY	Heavier than air	
SOLUBILITY IN WATER	N.A.	
VOLATILE ORGANIC COMPOUNDS	(VOC Theoretical - As Packaged)	
3.44 lb/gal	413 g/l	Less Water and Federally Exempt Solvents
3.44 lb/gal	413 g/l	Emitted VOC

=====

## Section 10 -- STABILITY AND REACTIVITY

-----

STABILITY -- Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

=====

## Section 11 -- TOXICOLOGICAL INFORMATION

## CHRONIC HEALTH HAZARDS

Ethylbenzene is classified by IARC as possibly carcinogenic to humans (2B) based on inadequate evidence in humans and sufficient evidence in laboratory animals. Lifetime inhalation exposure of rats and mice to high ethylbenzene concentrations resulted in increases in certain types of cancer, including kidney tumors in rats and lung and liver tumors in mice. These effects were not observed in animals exposed to lower concentrations. There is no evidence that ethylbenzene causes cancer in humans.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver, urinary and reproductive systems.

Rats exposed to titanium dioxide dust at 250 mg./m3 developed lung cancer, however, such exposure levels are not attainable in the workplace.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

=====

## TOXICOLOGY DATA

Continued on page 5

CAS No.	Ingredient Name				
64742-89-8	V. M. & P. Naphtha	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
25013-15-4	Vinyl Toluene	LC50	RAT	4HR	Not Available
		LD50	RAT		2255 mg/kg
100-41-4	Ethylbenzene	LC50	RAT	4HR	Not Available
		LD50	RAT		3500 mg/kg
1330-20-7	Xylene	LC50	RAT	4HR	5000 ppm
		LD50	RAT		4300 mg/kg
14807-96-6	Talc	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
7727-43-7	Barium Sulfate	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
13463-67-7	Titanium Dioxide	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
1314-13-2	Zinc Oxide	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available

Section 12 -- ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

No data available.

Section 13 -- DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

Section 14 -- TRANSPORT INFORMATION

No data available.

Section 15 -- REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

Continued on page 6



CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
100-41-4	Ethylbenzene	1	
1330-20-7	Xylene	6	
	Zinc Compound	7	4.8

## CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

## TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

## Section 16 -- OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.